

## **IP66 Rated**

2.0 Megapixel High Speed PTZ Dome Camera

## The ZEBRA Z-PT7E122S200

is a 2MP PTZ IP camera designed for indoor or outdoor applications. Features such as True Day/Night, 22x optical zoom and pattern tour provide full coverage for any large outdoor area, including parking lots or street views. ONVIF and 802.3at PoE + ensure compatibility with virtually any system.





- 1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
  - H.264 Compression Method
  - 22X Optical Zoom (3.9mm-85.5mm)
    - 8Pcs Array IR LEDS
    - IR Distance 120m Max. •
  - ONVIF compliant for maximum compatibility
    - Power Over Ethernet + (802.3at)

IP66 Outdoor





## **Z-PT7E122S200**

2.0 Megapixel High Speed PTZ Dome Camera



| Model NO.                 | Z-PT7E122S200   |
|---------------------------|---|
| Camera                    |   |
| Image Sensor              | 1/2.9" SONY Low Illumination 2.1MP CMOS Sensor  |
| Main processor            | HISILICON Hi3516C   |
| Resolution                | 2 MP 1080P  |
| Compression               | H.264   |
| TV System                 | PAL/NTSC  |
| S/N Ratio                 | ≥50dB   |
| Video Output              | Network   |
| Lens                      |   |
| Focus Length              | 3.9mm-85.5mm  |
| Focus Control             | 22X Optical Zoom  |
| Night Vision              |   |
| Infrared LED              | ⊄ 42 x 8 PCS Long Range IR LED  |
| Infrared Distance         | 120M  |
| Auto Control IR LED       | PWM   |
| Network                   |   |
| Ethernet                  | Built-in RJ45 network interface, support 10M/100M IP DATA                                   |
| Network Protocol          | TCP/IP , TTP , NTP , IGMP , DHCP , UDP , SMTP , RTP , RTSP , ARP , DDNS , DNS , PPPoE , P2P |
| ONVIF                     | Support   |
| POE                       | Support IEEE 802.3af  |
| IE Brower                 | IE8-11, Google Chrome, Firefox, Safari, Mac Safari  |
| PTZ Features              |   |
| Horizontal Rotation Speed | 120°/ S   |
| Horizontal Rotation Range | 0°~360°   |
| Tilt Rotation Speed       | 60°/S   |
| Tilt Rotation Range       | 0° ~ 90°  |
| A-B Scan                  | Support   |
| Auto Flip                 | Support   |
| 360° Scan                 | Support   |
| Preset Points             | 220   |
| Guard Tours               | 3 groups  |
| Guard Points              | Max.16 points   |
| General                   |   |
| Housing                   | Weatherproof IP66   |
| Operating Temperature     | Indoor: 0°~ +40° Outdoor: -40°~ +60°  |
| Operating Humidity        | ≤90% Non-Condensing   |
| Heater & Blower           | Auto temperature control  |
| Power                     | DC12V/4A  |
| Lightning Protection      | Transient voltage 6000V   |
| Dimension                 | 31x31x44(cm)  |
| Weight                    | 10.2Kgs   |
|                           |   |

## **SUGGESTED APPLICATIONS**

- Public places
- Commercial
- Streets
- Government buildings
- Military
- many more...



©2013 Zebra Security, Inc. All rights reserved. All products and names mentioned ae the property of their rrespecte owners. While Zebra has made every efffort at the time of publication to ensure the accuracy of the information povided herein, product specifications, configurations, priceystem/component/ent/options availability are all subject to change without notice.

Zebra Security Inc. USA Surveillance & IP video products, imaging systems division 120 Comostock Ave Station Island New York 10314, USA www.zebrasecurity.us

Made in Taiwan





