



# Z-PTDKS500

## IP66 Rated

5 MEGAPIXEL 10X PTZ  
OUTDOOR BULLET  
IP CAMERA



*The ZEBRA Z-PTDKS500 is a 5MP PTZ IP camera designed for indoor or outdoor applications. Features such as True Day/Night, 10x optical zoom and pattern tour provide full coverage for any large outdoor area, including parking lots or street views. ONVIF and 802.3at PoE + ensure compatibility with virtually any system.*



## FEATURES

- 1/2.5" Aptina 5.1MP High Performance CMOS Sensor
- H.264/H.265 Compression Method
- 10X Optical Zoom (f=5.1mm-51mm)
- 4PCS Array IR LEDS + 2PCS Laser Lamp
- IR Distance 100m Max.
- ONVIF compliant for maximum compatibility
- Power Over Ethernet + (802.3at)



# Z-PTDKS500

5 MEGAPIXEL 10X PTZ OUTDOOR  
BULLET IP CAMERA



## SUGGESTED APPLICATIONS

- Public places
- Commercial
- Streets
- Government buildings
- Military
- many more...



| Model NO.                 | Z-PTDKS500   |
|---------------------------|--|
| <b>Camera</b>             |  |
| Image Sensor              | 1/2.5" Aptina 5.1MP High Performance CMOS Sensor                               |
| Main processor            | HISILICON Hi3516D  |
| Resolution                | 5 Megapixel  |
| Compression               | H.264/H.265  |
| TV System                 | PAL/NTSC   |
| S/N Ratio                 | ≥50dB  |
| Video Output              | Network  |
| <b>Lens</b>               |  |
| Focus Length              | 5.1mm-51mm   |
| Focus Control             | 10X Optical Zoom   |
| <b>Night Vision</b>       |  |
| Infrared LED              | 4PCS Array IR LEDs + 2PCS Laser Lamp   |
| Infrared Distance         | 100M   |
| Auto Control IR LED       | PWM  |
| <b>Network</b>            |  |
| Ethernet                  | Built-in RJ45 network interface, support 10M/100M IP DATA                      |
| Protocol                  | TCP/IP, TTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P |
| ONVIF                     | Support  |
| P2P                       | YES, Support QR Code   |
| POE                       | Support IEEE 802.3af   |
| IE Brower                 | IE8-11, Google Chrome, Firefox, Safari, Mac Safari                             |
| Smart Phone               | iPhone, iPad, Android, Android Pad   |
| <b>PTZ Features</b>       |  |
| Horizontal Rotation Speed | 30°/S  |
| Horizontal Rotation Range | 0°~200°  |
| Tilt Rotation Speed       | 25°/S  |
| Tilt Rotation Range       | -45°~40°   |
| A-B Scan                  | Support  |
| Preset Points             | 220  |
| Guard Tours               | 3 groups   |
| Guard Points              | Max.16 points  |
| <b>General</b>            |  |
| Housing                   | Weatherproof IP66  |
| Operating Temperature     | Indoor: 0°~ +40° Outdoor: -40°~ +60°   |
| Operating Humidity        | ≤90% Non Condensing  |
| Heater & Blower           | Auto temperature control   |
| Power                     | DC12V/3A   |
| Lightning Protection      | Transient voltage 6000V  |
| Dimension                 | 39.6x19.6x16(cm)   |
| Weight                    | 3Kgs   |
| Made in Taiwan            |  |

©2013 Zebra Security, Inc. All rights reserved. All products and names mentioned are the property of their respective owners. While Zebra has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, price system/component/ent/options availability are all subject to change without notice.

**Zebra Security Inc. USA**  
Surveillance & IP video products, imaging systems division  
120 Comostock Ave Station Island  
New York 10314, USA  
www.zebrasecurity.us

